

Declaration of Performance according to Regulation (EU) 305/2011

No.: LE29102334



- productLina 120 h, Lina TV 120 h
- intended use
space heating in residential buildings without supply of hot water
- trade mark
Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Gewerbepark 18 | 49143 D-Bissendorf
info@camina-schmid.de | www.camina-schmid.de
- authorized representative
-
- system of assessment and verification
of constancy of performance of the
construction product
system 3
- The notified laboratory
RRF - Rhein-Ruhr Feuerstätten Prüfstelle GmbH
D-46047 Oberhausen – notified body number: 1625
performed of the product type on the basis of type testing
under system 3.
RRF - 29 10 2334
report
- declaration of performance

Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007
essential characteristics	performance
fire safety	pass
reaction to fire	A1
minimum safety distance to combustible material	radiation area 800 mm
minimum insulation thickness (based on SILCA® 250KM) to adjacent combustible material / distance between insert and insulation	floor - / 0 mm rear 60 mm / 100 mm sides 60 mm / 100 mm
risk of burning fuel falling out	pass
cleanability	pass
emission of combustion products (log of wood)	CO 1250 mg/Nm ³ 0,1 %
surface temperature	pass
electrical safety	not applicable
release of dangerous substance	NPD
max. operation pressure	not applicable
flue gas temperature at nominal heat output (log of wood)	365 °C
mechanical resistance (to carry a chimney/flue)	NPD
thermal output / efficiency	pass
nominal heat output	10 kW
room heating output	10 kW
water heating output	not applicable
efficiency (log of wood)	80,4 %

- The performance of the product is in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer

Colin Rokossa | Managing Director
Bissendorf, 11.01.2023

product

Lina 120 h, Lina TV 120 h

test report	RRF - 29 10 2334		
fuel	log of wood		
triple value for nominal heat output (closed operation)			
flue gas mass flow	7,9 g/s		
flue gas temperature	365 °C		
required draught	12 Pa		
emission values (related to 13% O2) and efficiency at nominal heat output (closed operation)			
CO	1250 mg/Nm³	833 mg/MJ	0,1 %
PM	27 mg/Nm³	17 mg/MJ	
NOx	81 mg/Nm³	51 mg/MJ	
OGC	94 mg/Nm³	60 mg/MJ	
efficiency	80,4 %		
Please read the installation and operating instructions!			