

Declaration of Performance according to Regulation (EU) 305/2011

No.: LE29061074-1



- product: Lina 67 s/h, Lina TV 67 s/h
- intended use: space heating in residential buildings without supply of hot water
- trade mark: Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Gewerbepark 18 | 49143 D-Bissendorf
info@camina-schmid.de | www.camina-schmid.de
- authorized representative: -
- system of assessment and verification of constancy of performance of the construction product: system 3
- The notified laboratory: RRF - Rhein-Ruhr Feuerstätten Prüfstelle GmbH
D-46047 Oberhausen – notified body number: 1625
performed of the product type on the basis of type testing under system 3.
RRF - 29 06 1074
report
- declaration of performance

| Harmonized technical specification | EN 13229:2001/A2:2004/AC:2007 |
|--|---|
| essential characteristics | performance |
| fire safety | pass |
| reaction to fire | A1 |
| minimum safety distance to combustible material | radiation area 800 mm |
| minimum insulation thickness (based on SILCA® 250KM) to adjacent combustible material / distance between insert and insulation | floor - / 0 mm rear 60 mm / 90 mm sides 60 mm / 90 mm |
| risk of burning fuel falling out | pass |
| cleanability | pass |
| emission of combustion products (log of wood) | CO 875 mg/Nm ³ 0,07 % |
| surface temperature | pass |
| electrical safety | not applicable |
| release of dangerous substance | NPD |
| max. operation pressure | not applicable |
| flue gas temperature at nominal heat output (log of wood) | 320 °C |
| mechanical resistance (to carry a chimney/flue) | NPD |
| thermal output / efficiency | pass |
| nominal heat output | 9 kW |
| room heating output | 9 kW |
| water heating output | not applicable |
| efficiency (log of wood) | 78,2 % |

- The performance of the product is in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer

Colin Rokossa | Managing Director
Bissendorf, 11.01.2023

product

Lina 67 s/h, Lina TV 67 s/h

| | | | |
|---|------------------------|-----------|--------|
| test report | RRF - 29 06 1074 | | |
| fuel | log of wood | | |
| triple value for nominal heat output (closed operation) | | | |
| flue gas mass flow | 9,1 g/s | | |
| flue gas temperature | 320 °C | | |
| required draught | 12 Pa | | |
| emission values (related to 13% O2) and efficiency at nominal heat output (closed operation) | | | |
| CO | 875 mg/Nm ³ | 563 mg/MJ | 0,07 % |
| PM | 39 mg/Nm ³ | 25 mg/MJ | |
| NOx | 113 mg/Nm ³ | 71 mg/MJ | |
| OGC | 61 mg/Nm ³ | 39 mg/MJ | |
| efficiency | 78,2 % | | |
| Please read the installation and operating instructions! | | | |